

## TYRES

Product group	Tyres
Item number	15225140
Valid tyre size	480 / 70 R 30
LI / SI / PR	150 A8 / 144 E
TL/TT	TL
Brand	Alliance
Tread pattern	370



## Notes and features

- Agricultural wide-base tyre of the 70 series for tractors in the low-performance range up to large tractors with over 200 hp.
- All-round tyre for use on farmland and grassland.
- Offers higher load capacities with the same inflation pressure in comparison to 85 standard tyres.
- R-1W drive tread pattern with higher tread depth for improved traction and high mileage.

## Technical Informations

Item number	15225140
EAN	7291050021265
Valid tyre size	480 / 70 R 30
Alternative size 1	19.5LR30
LI / SI / PR	150 A8 / 144 E
TL/TT	TL
Brand	Alliance
Tread pattern	370
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	112,14
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	2,40
Section width (mm)	479
Outer diameter of tyre [mm].	1474
Stat. radius (SLR) [mm]	676
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4564
Tread depth (mm)	46,0
Number of lugs	17x2
Lug width (mm)	37
Tyre capacity 75% [ltr.]	292.5
Guarantee period	7 years

E-Ready

No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		2,40	
144 E	2800	70		2,40	