

## TYRES

|                 |                  |
|-----------------|------------------|
| Product group   | Tyres            |
| Item number     | 15225147         |
| Valid tyre size | VF 600 / 70 R 30 |
| LI / SI / PR    | 170 D            |
| TL/TT           | TL               |
| Brand           | Alliance         |
| Tread pattern   | Agriflex 372 +   |



## Notes and features

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.

## Technical Informations

|                              |                  |
|------------------------------|------------------|
| Item number                  | 15225147         |
| EAN                          | 7291050068994    |
| Valid tyre size              | VF 600 / 70 R 30 |
| LI / SI / PR                 | 170 D            |
| TL/TT                        | TL               |
| Brand                        | Alliance         |
| Tread pattern                | Agriflex 372 +   |
| Carcass properties           | Steel Belted     |
| Antistatic                   | No               |
| Tyre colour                  | Black            |
| ECE regulation number        | ECE 106          |
| Nettogewicht [kg] (gültig)   | 222,85           |
| Recommended rim size         | 21               |
| Permitted rim size           | 20               |
| Maximum air pressure [bar].  | 2,40             |
| Section width (mm)           | 634              |
| Tread width (mm)             | 600              |
| Outer diameter of tyre [mm]. | 1605             |
| Stat. radius (SLR) [mm]      | 703              |
| Speed Radius Index (SRI)     | 750              |
| Rolling circumference [mm].  | 4712             |
| Tread depth (mm)             | 56,0             |
| Number of lugs               | 20x2             |
| Tyre capacity 75% [ltr.]     | 498              |
| Guarantee period             | 10 years         |
| E-Ready                      | No               |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 170 D | 6000               | 65           |               | 2,40                     |              |