Bohnenkamp Moving Professionals

TYRES

| Product group | Tyres |
|-----------------|-----------------|
| Item number | 15225177 |
| Valid tyre size | 600 / 70 R 34 |
| LI / SI / PR | 163 A8 / 160 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agristar 378 XL |





Notes and features

- Super volume tyre for high-performance tractors from . approx. 200 hp and harvesters.
- Designed for versatile applications. •
- Comfortable on-road handling and high traction combined with very good self-cleaning properties in field operations.
- Built-in steel belts for extra stability, protection against . punctures and large contact area.
- Innovative rubber compound for a longer service life and • flexible sidewalls (for air pressure adjustment).

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 15225177 |
|------------------------------|-----------------|
| EAN | 7291050062480 |
| Valid tyre size | 600 / 70 R 34 |
| LI / SI / PR | 163 A8 / 160 D |
| | |
| TL/TT | |
| Brand | Alliance |
| Tread pattern | Agristar 378 XL |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 171,39 |
| Recommended rim size | 20 |
| Permitted rim size | 18 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 610 |
| Outer diameter of tyre [mm]. | 1705 |
| Stat. radius (SLR) [mm] | 770 |
| Rolling circumference [mm]. | 5118 |
| Tread depth (mm) | 51,0 |
| Number of lugs | 20x2 |
| Tyre capacity 75% [ltr.] | 496 |
| Guarantee period | 7 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 163 A8 | 4875 | 40 | | 2,40 | |
| 160 D | 4500 | 65 | | 2,40 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.