# Bohnenkamp Moving Professionals

19.09.2024

#### TYRES

Product group	Tyres
Item number	15225237
Valid tyre size	580 / 70 R 38
LI / SI / PR	180 A8
TL/TT	TL
Brand	Alliance
Tread pattern	370





#### Notes and features

- Agricultural wide-base tyre of the 70 series for tractors in the low-performance range up to large tractors with over 200 hp.
- All-round tyre for use on farmland and grassland.
- Offers higher load capacities with the same inflation pressure in comparison to 85 standard tyres.
- R-1W drive tread pattern with higher tread depth for improved traction and high mileage.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	15225237
EAN	7291050022118
Valid tyre size	580 / 70 R 38
LI / SI / PR	180 A8
TL/TT	TL
Brand	Alliance
Tread pattern	370
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	218,49
Recommended rim size	18
Maximum air pressure [bar].	4,60
Section width (mm)	577
Outer diameter of tyre [mm].	1817
Stat. radius (SLR) [mm]	816
Rolling circumference [mm].	5343
Tread depth (mm)	58,0
Number of lugs	18x2
Lug width (mm)	44-52
Tyre capacity 75% [ltr.]	547.5
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180 A8	8000	40		4,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.