Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	15225248	
Valid tyre size	VF 710 / 70 R 38 CFO	
LI / SI / PR	178 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 372 +	



≈Alliance

Notes and features

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number15225248EAN7291050080262Valid tyre sizeVF 710 / 70 R 38 CFOLl / SI / PR178 DTL/TTTLBrandAllianceTread patternAgriflex 372 +Carcass propertiesSteel Belted
Valid tyre size VF 710 / 70 R 38 CFO LI / SI / PR 178 D TL/TT TL Brand Alliance Tread pattern Agriflex 372 +
LI / SI / PR 178 D TL/TT TL Brand Alliance Tread pattern Agriflex 372 +
TL/TT TL Brand Alliance Tread pattern Agriflex 372 +
Brand Alliance Tread pattern Agriflex 372 +
Tread pattern Agriflex 372 +
Carcass properties Steel Belted
Antistatic No
Tyre colour Black
ECE regulation number ECE 106
Nettogewicht [kg] (gültig) 290,60
Recommended rim size 25
Permitted rim size 23, 24
Maximum air pressure [bar]. 1,60
Section width (mm) 720
Outer diameter of tyre [mm]. 1959
Stat. radius (SLR) [mm] 843
Speed Radius Index (SRI) 925
Rolling circumference [mm]. 5735
Tread depth (mm) 61,0
Number of lugs 19x2
Tyre capacity 75% [ltr.] 839.25
Guarantee period 10 years
E-Ready No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 D	7500	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.