

TYRES

Product group	Tyres	
Item number	15225269	
Valid tyre size	IF 710 / 70 R 42 CFO	
LI / SI / PR	179 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 372	



Notes and features

- The Alliance 372 is an IF tyre for high-performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.



Technical Informations

Item number	15225269
EAN	7291050061094
Valid tyre size	IF 710 / 70 R 42 CFO
LI / SI / PR	179 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	336,40
Recommended rim size	25
Permitted rim size	24, 23
Maximum air pressure [bar].	2,40
Section width (mm)	751
Outer diameter of tyre [mm].	2058
Stat. radius (SLR) [mm]	929
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6134
Tread depth (mm)	63,0
Number of lugs	20x2
Lug width (mm)	34
Tyre capacity 75% [ltr.]	900
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		2,40	