

TYRES

Product group	Tyres
Item number	15225280
Valid tyre size	650 / 75 R 32
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375





Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.



Technical Informations

Item number	15225280
EAN	7291050046398
Valid tyre size	650 / 75 R 32
Alternative size 1	24.5R32
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	258,93
Recommended rim size	21
Maximum air pressure [bar].	3,20
Section width (mm)	670
Outer diameter of tyre [mm].	1830
Stat. radius (SLR) [mm]	836
Rolling circumference [mm].	5442
Tread depth (mm)	58,0
Tyre capacity 75% [ltr.]	704.25
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		3,20	
172 B	6300	50		3,20	