

## **TYRES**

Product group	Tyres	
Item number	15225283	
Valid tyre size	800 / 70 R 32 CHO	
LI / SI / PR	175 A8 / 175 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agristar 375	





## Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.



## **Technical Informations**

Item number	15225283
EAN	7291050061711
Valid tyre size	800 / 70 R 32 CHO
LI / SI / PR	175 A8 / 175 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	382,16
Recommended rim size	27
Permitted rim size	25
Maximum air pressure [bar].	2,40
Section width (mm)	780
Outer diameter of tyre [mm].	1935
Stat. radius (SLR) [mm]	877
Rolling circumference [mm].	5706
Tread depth (mm)	65,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	926
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A8	6900	40		2,40	
175 B	6900	50		2,40	