

TYRES

Product group	Tyres
Item number	15226012
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Alliance
Tread pattern	570





Notes and features

- Radial multipurpose tyre for a wide variety of applications.
- Specially suited for use on harvesters.
- Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
- Radial textile casing with steel belt reinforcement.



Technical Informations

Item number 15226012 EAN 8903635013198 Valid tyre size 460 / 70 R 24 Alternative size 1 17.5LR24 LI/SI/PR 159 A8 / 159 B TL/TT TL Brand Alliance Tread pattern 570 Antistatic No Tyre colour Black
Valid tyre size 460 / 70 R 24 Alternative size 1 17.5LR24 LI / SI / PR 159 A8 / 159 B TL/TT TL Brand Alliance Tread pattern 570 Antistatic No
Alternative size 1 17.5LR24 LI / SI / PR 159 A8 / 159 B TL/TT TL Brand Alliance Tread pattern 570 Antistatic No
LI / SI / PR 159 A8 / 159 B TL/TT TL Brand Alliance Tread pattern 570 Antistatic No
TL/TT TL Brand Alliance Tread pattern 570 Antistatic No
Brand Alliance Tread pattern 570 Antistatic No
Tread pattern 570 Antistatic No
Antistatic No
Tyre colour Black
ECE regulation number ECE 106
Nettogewicht [kg] (gültig) 91,20
Recommended rim size 15
Permitted rim size 14
Maximum air pressure [bar]. 4,00
Section width (mm) 445
Outer diameter of tyre [mm]. 1245
Stat. radius (SLR) [mm] 564
Rolling circumference [mm]. 3682
Tread depth (mm) 36,9
Number of lugs 19x2
E-Ready No



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
159 B	4375	50		4,00	