

TYRES

Product group	Tyres
Item number	15226020
Valid tyre size	19.5L R 24
LI / SI / PR	156 A8 / 153 B
TL/TT	TL
Brand	Alliance
Tread pattern	570





Notes and features

- Radial multipurpose tyre for a wide variety of applications.
- Specially suited for use on harvesters.
- Agricultural tractor pattern for good traction when operating on arable land.
- High load capacities even with low inflation pressures.
- Radial textile casing with steel belt reinforcement.



Technical Informations

Item number	15226020
EAN	8903635008132
Valid tyre size	19.5L R 24
LI / SI / PR	156 A8 / 153 B
TL/TT	TL
Brand	Alliance
Tread pattern	570
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	105,84
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	3,00
Section width (mm)	495
Outer diameter of tyre [mm].	1320
Stat. radius (SLR) [mm]	600
Rolling circumference [mm].	3912
Tread depth (mm)	35,0
Lug width (mm)	32
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A8	4000	40		3,00	
	3640	50		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.