

TYRES

Product group	Tyres
Item number	15226100
Valid tyre size	230 / 95 R 32
LI / SI / PR	131 A8 / 128 D
TL/TT	TL
Brand	Alliance
Tread pattern	350





Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



Technical Informations

Item number	15226100
EAN	8903635015093
Valid tyre size	230 / 95 R 32
Alternative size 1	9.5R32
LI / SI / PR	131 A8 / 128 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	42,80
Recommended rim size	8
Permitted rim size	7
Maximum air pressure [bar].	3,60
Section width (mm)	228
Outer diameter of tyre [mm].	1251
Stat. radius (SLR) [mm]	582
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3821
Tread depth (mm)	34,5
Number of lugs	23x2
Lug width (mm)	25
Tyre capacity 75% [ltr.]	68
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 A8	1950	40		3,60	
128 D	1800	65		3,60	