

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15226100 |
| Valid tyre size | 230 / 95 R 32 |
| LI / SI / PR | 131 A8 / 128 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 350 |



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 15226100 |
| EAN | 8903635015093 |
| Valid tyre size | 230 / 95 R 32 |
| Alternative size 1 | 9.5R32 |
| LI / SI / PR | 131 A8 / 128 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 350 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 42,80 |
| Recommended rim size | 8 |
| Permitted rim size | 7 |
| Maximum air pressure [bar]. | 3,60 |
| Section width (mm) | 228 |
| Outer diameter of tyre [mm]. | 1251 |
| Stat. radius (SLR) [mm] | 582 |
| Speed Radius Index (SRI) | 600 |
| Rolling circumference [mm]. | 3821 |
| Tread depth (mm) | 34,5 |
| Number of lugs | 23x2 |
| Lug width (mm) | 25 |
| Tyre capacity 75% [ltr.] | 68 |
| Guarantee period | 7 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 131 A8 | 1950 | 40 | | 3,60 | |
| 128 D | 1800 | 65 | | 3,60 | |