

## **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 15226125       |
| Valid tyre size | 270 / 95 R 32  |
| LI / SI / PR    | 135 A8 / 132 D |
| TL/TT           | TL             |
| Brand           | Alliance       |
| Tread pattern   | 350            |





## Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



## **Technical Informations**

| Item number                  | 15226125       |
|------------------------------|----------------|
| EAN                          | 8903635011873  |
| Valid tyre size              | 270 / 95 R 32  |
| Alternative size 1           | 11.2R32        |
| LI / SI / PR                 | 135 A8 / 132 D |
| TL/TT                        | TL             |
| Brand                        | Alliance       |
| Tread pattern                | 350            |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 51,13          |
| Recommended rim size         | 10             |
| Permitted rim size           | 9, 8           |
| Maximum air pressure [bar].  | 3,60           |
| Section width (mm)           | 284            |
| Outer diameter of tyre [mm]. | 1300           |
| Stat. radius (SLR) [mm]      | 604            |
| Speed Radius Index (SRI)     | 625            |
| Rolling circumference [mm].  | 3946           |
| Tread depth (mm)             | 36,5           |
| Number of lugs               | 23x2           |
| Tyre capacity 75% [Itr.]     | 96             |
| Guarantee period             | 7 years        |
| E-Ready                      | No             |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 135 A8 | 2180               | 40           |               | 3,60                        |              |
| 132 D  | 2000               | 65           |               | 3,60                        |              |