

TYRES

Product group	Tyres
Item number	15226205
Valid tyre size	230 / 95 R 42
LI / SI / PR	136 A8 / 133 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	15226205
EAN	8903635015925
Valid tyre size	230 / 95 R 42
Alternative size 1	9.5R42
LI / SI / PR	136 A8 / 133 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	51,60
Recommended rim size	W7
Permitted rim size	W8
Maximum air pressure [bar].	4,00
Section width (mm)	228
Outer diameter of tyre [mm].	1505
Stat. radius (SLR) [mm]	712
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4618
Tread depth (mm)	34,5
Number of lugs	27x2
Tyre capacity 75% [litr.]	85
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 A8	2240	40		4,00	
133 D	2060	65		4,00	