

TYRES

Product group	Tyres
Item number	15226255
Valid tyre size	230 / 95 R 44
LI / SI / PR	137 A8 / 134 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	15226255
EAN	8903635011903
Valid tyre size	230 / 95 R 44
Alternative size 1	9.5R44
LI / SI / PR	137 A8 / 134 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	56,48
Recommended rim size	W7
Permitted rim size	W8
Maximum air pressure [bar].	3,60
Section width (mm)	241
Outer diameter of tyre [mm].	1550
Stat. radius (SLR) [mm]	745
Rolling circumference [mm].	4821
Tread depth (mm)	38,0
Tyre capacity 75% [ltr.]	89
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
137 A8	2300	40		3,60	
134 D	2120	65		3,60	