

## **TYRES**

Product group	Tyres
Item number	15226300
Valid tyre size	320 / 90 R 46
LI / SI / PR	151 A8 / 148 D
TL/TT	TL
Brand	Alliance
Tread pattern	350





## Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



## **Technical Informations**

Item number	15226300
EAN	7291050016346
Valid tyre size	320 / 90 R 46
Alternative size 1	12.4R46
LI / SI / PR	151 A8 / 148 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	83,04
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	3,60
Section width (mm)	315
Outer diameter of tyre [mm].	1727
Stat. radius (SLR) [mm]	807
Rolling circumference [mm].	5294
Tread depth (mm)	38,0
Number of lugs	30x2
Lug width (mm)	28
Tyre capacity 75% [ltr.]	201.75
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,60	
148 D	3150	65		3,60	