

TYRES

Product group	Tyres
Item number	15226306
Valid tyre size	300 / 95 R 46
LI / SI / PR	151 A8 / 148 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	15226306
EAN	8903635011910
Valid tyre size	300 / 95 R 46
Alternative size 1	12.4R46
LI / SI / PR	151 A8 / 148 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	82,92
Recommended rim size	11
Permitted rim size	9, 10
Maximum air pressure [bar].	3,60
Section width (mm)	315
Outer diameter of tyre [mm].	1727
Stat. radius (SLR) [mm]	808
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5294
Contact area [cm ²]	853.7
Tread depth (mm)	38,0
Number of lugs	30x2
Tyre capacity 75% [ltr.]	171
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,60	
148 D	3150	65		3,60	