

## TYRES

Product group	Tyres
Item number	15226313
Valid tyre size	IF 320 / 105 R 46
LI / SI / PR	166 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354



Bohnenkamp  
■ ■ ● Moving Professionals

 **ALLIANCE**

## Notes and features

- The Alliance Agriflex 354 is a row crop tyre with IF technology for tractors, self-propelled and towed field sprayers.
- As an IF tyre, it has 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belt construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.

## Technical Informations

Item number	15226313
EAN	7291050063999
Valid tyre size	IF 320 / 105 R 46
LI / SI / PR	166 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	136,49
Recommended rim size	11
Permitted rim size	10, 12
Maximum air pressure [bar].	4,80
Section width (mm)	338
Outer diameter of tyre [mm].	1844
Stat. radius (SLR) [mm]	857
Speed Radius Index (SRI)	900
Rolling circumference [mm].	5572
Tread depth (mm)	45,6
Number of lugs	34x2
Tyre capacity 75% [ltr.]	245
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		4,80	