

## TYRES

Product group	Tyres
Item number	15226322
Valid tyre size	380 / 90 R 46
LI / SI / PR	175 A8 / 172 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



## Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

## Technical Informations

Item number	15226322
EAN	7291050043724
Valid tyre size	380 / 90 R 46
Alternative size 1	14.9R46
LI / SI / PR	175 A8 / 172 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	154,31
Recommended rim size	13
Permitted rim size	11, 12
Maximum air pressure [bar].	5,80
Section width (mm)	378
Outer diameter of tyre [mm].	1824
Stat. radius (SLR) [mm]	864
Speed Radius Index (SRI)	900
Rolling circumference [mm].	5633
Tread depth (mm)	40,5
Tyre capacity 75% [litr.]	315
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A8	6900	40		5,80	
172 D	6300	65		5,80	