

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 15226328 |
| Valid tyre size | VF 520 / 85 R 46 |
| LI / SI / PR | 170 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 354 + |



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**
ENGINEERED TO KEEP YOU AHEAD

Notes and features

- The Alliance Agriflex 354 is a row crop tyre with VF technology for tractors, self-propelled and towed field sprayers.
- As a VF tyre, it has 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belted construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 15226328 |
| EAN | 7291050070843 |
| Valid tyre size | VF 520 / 85 R 46 |
| LI / SI / PR | 170 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 354 + |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 231,50 |
| Recommended rim size | DW18L |
| Permitted rim size | DW16L |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 535 |
| Outer diameter of tyre [mm]. | 2052 |
| Stat. radius (SLR) [mm] | 906 |
| Speed Radius Index (SRI) | 975 |
| Rolling circumference [mm]. | 6050 |
| Tread depth (mm) | 53,0 |
| Number of lugs | 29x2 |
| Tyre capacity 75% [ltr.] | 606 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 170 D | 6000 | 65 | | 1,60 | |