

## **TYRES**

Product group	Tyres	
Item number	15226365	
Valid tyre size	270 / 95 R 48	
LI / SI / PR	145 A8 / 142 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	350	





## Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



## **Technical Informations**

Item number	15226365
EAN	8903635011736
Valid tyre size	270 / 95 R 48
Alternative size 1	11.2R48
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	72,71
Recommended rim size	10
Permitted rim size	9, 8
Maximum air pressure [bar].	3,60
Section width (mm)	284
Outer diameter of tyre [mm].	1710
Stat. radius (SLR) [mm]	814
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5319
Tread depth (mm)	32,0
Number of lugs	30x2
Tyre capacity 75% [Itr.]	136
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		3,60	
142 D	2650	65		3,60	