

TYRES

Product group	Tyres
Item number	15226669
Valid tyre size	270 / 95 R 44
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	Alliance
Tread pattern	350





Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



Technical Informations

Item number	15226669
EAN	8903635014409
Valid tyre size	270 / 95 R 44
Alternative size 1	11.2R44
LI / SI / PR	145 A8 / 142 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	70,81
Recommended rim size	10
Permitted rim size	8, 9
Maximum air pressure [bar].	4,00
Section width (mm)	275
Outer diameter of tyre [mm].	1632
Stat. radius (SLR) [mm]	770
Speed Radius Index (SRI)	800
Rolling circumference [mm].	4992
Contact area [cm²]	609.2
Tread depth (mm)	40,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	127
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		4,00	
142 D	2650	65		4,00	