

## **TYRES**

Product group	Tyres
Item number	15226677
Valid tyre size	380 / 105 R 50
LI / SI / PR	171 A8 / 168 D
TL/TT	TL
Brand	Alliance
Tread pattern	350





## Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



## **Technical Informations**

Item number	15226677
EAN	7291050059398
Valid tyre size	380 / 105 R 50
LI / SI / PR	171 A8 / 168 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	180,86
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	4,40
Section width (mm)	405
Outer diameter of tyre [mm].	2050
Stat. radius (SLR) [mm]	955
Rolling circumference [mm].	6214
Tread depth (mm)	39,0
Number of lugs	33x2
Tyre capacity 75% [ltr.]	490
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
171 A8	6150	40		4,40	
168 D	5600	65		4,40	