

## TYRES

Product group	Tyres
Item number	15226682
Valid tyre size	VF 480 / 95 R 50
LI / SI / PR	176 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354 +



Bohnenkamp  
■ ■ ● Moving Professionals

 **ALLIANCE**  
ENGINEERED TO KEEP YOU AHEAD

## Notes and features

- The Alliance Agriflex 354 is a row crop tyre with VF technology for tractors, self-propelled and towed field sprayers.
- As a VF tyre, it has 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belted construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.

**Technical Informations**

<b>Item number</b>	15226682
<b>EAN</b>	7291050071635
<b>Valid tyre size</b>	VF 480 / 95 R 50
<b>LI / SI / PR</b>	176 D
<b>TL/TT</b>	TL
<b>Brand</b>	Alliance
<b>Tread pattern</b>	Agriflex 354 +
<b>Carcass properties</b>	Steel Belted
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	ECE 106
<b>Nettogewicht [kg] (gültig)</b>	224,18
<b>Recommended rim size</b>	16
<b>Permitted rim size</b>	15
<b>Maximum air pressure [bar].</b>	2,40
<b>Section width (mm)</b>	485
<b>Outer diameter of tyre [mm].</b>	2187
<b>Stat. radius (SLR) [mm]</b>	977.00
<b>Speed Radius Index (SRI)</b>	1075
<b>Rolling circumference [mm].</b>	6511
<b>Tread depth (mm)</b>	53,0
<b>Number of lugs</b>	32x2
<b>Tyre capacity 75% [ltr.]</b>	585.75
<b>Guarantee period</b>	10 years
<b>E-Ready</b>	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 D	7100	65		2,40	