

TYRES

Product group	Tyres
Item number	15226685
Valid tyre size	300 / 95 R 52
LI / SI / PR	159 A8 / 156 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	15226685
EAN	7291050060141
Valid tyre size	300 / 95 R 52
Alternative size 1	12.4R52
LI / SI / PR	159 A8 / 156 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	114,07
Recommended rim size	W10
Permitted rim size	W8, W9
Maximum air pressure [bar].	4,80
Section width (mm)	310
Outer diameter of tyre [mm].	1890
Stat. radius (SLR) [mm]	887
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5781
Tread depth (mm)	38,0
Tyre capacity 75% [ltr.]	213
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,80	
156 D	4000	65		4,80	