Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15226691
Valid tyre size	VF 380 / 105 R 50
LI / SI / PR	179 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 363 +



Notes and features

- The Alliance 363+ is a VF row crop tyre for heavy, selfpropelled field sprayers and tractors.
- It offers up to 40% higher load capacity at the same inflation pressure or the same load capacity at up to 40% reduced inflation pressure compared with a standard tyre.
- The directional tread pattern design, divided in separate blocks, enables good grip on soft surfaces.
- The increased number of lugs and block distribution on the tread pattern ensure good ride comfort and low rolling resistance on roads.
- Its large contact area provides high traction, reduced fuel consumption and low soil compaction.
- The steel belted casing enables uniform ground pressure distribution and protection against damages, thus ensuring a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number 15226691 EAN 8903635047124 Valid tyre size VF 380 / 105 R 50 LI / SI / PR 179 D	
Valid tyre size VF 380 / 105 R 50	
LI/SI/PR 179 D	
TL/TT TL	
Brand Alliance	
Tread pattern Agriflex 363 +	
Carcass properties Steel Belted	
Antistatic No	
Tyre colour Black	
Nettogewicht [kg] (gültig) 191,20	
Recommended rim size W13	
Maximum air pressure [bar]. 4,40	
Section width (mm) 400	
Outer diameter of tyre [mm]. 2050	
Stat. radius (SLR) [mm] 946	
Rolling circumference [mm]. 6206	
Tread depth (mm)40,0	
Tyre capacity 75% [ltr.] 371.85	
Guarantee period 10 years	
E-Ready No	

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		4,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.