

TYRES

Product group	Tyres	
Item number	15226695	
Valid tyre size	VF 230 / 115 R 54	
LI / SI / PR	151 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 354 +	





Notes and features

- The Alliance Agriflex 354 is a row crop tyre with VF technology for tractors, self-propelled and towed field sprayers.
- As a VF tyre, it has 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped
- Its large contact area and steel belted construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.



Technical Informations

Item number	15226695
EAN	7291050085830
Valid tyre size	VF 230 / 115 R 54
LI / SI / PR	151 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354 +
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	105,30
Recommended rim size	W8
Maximum air pressure [bar].	3,20
Section width (mm)	257
Outer diameter of tyre [mm].	1947
Stat. radius (SLR) [mm]	912
Rolling circumference [mm].	5931
Tread depth (mm)	46,0
Number of lugs	37x2
Tyre capacity 75% [ltr.]	154.8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 D	3450	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.