

## **TYRES**

Product group	Tyres	
Item number	15226700	
Valid tyre size	270 / 95 R 54	
LI / SI / PR	149 A8 / 146 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	350	





## Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



## **Technical Informations**

Item number	15226700
EAN	7291050043748
Valid tyre size	270 / 95 R 54
Alternative size 1	11.2R54
LI / SI / PR	149 A8 / 146 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	84,99
Recommended rim size	10
Permitted rim size	8, 9
Maximum air pressure [bar].	3,60
Section width (mm)	285
Outer diameter of tyre [mm].	1900
Stat. radius (SLR) [mm]	901
Rolling circumference [mm].	5826
Tread depth (mm)	36,0
Number of lugs	33x2
Lug width (mm)	26
Tyre capacity 75% [ltr.]	167.25
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		3,60	
146 D	3000	65		3,60	