

## **TYRES**

Product group	Tyres
Item number	15226701
Valid tyre size	270 / 95 R 54
LI / SI / PR	159 A8 / 156 D
TL/TT	TL
Brand	Alliance
Tread pattern	350





## Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



## **Technical Informations**

Item number	15226701
EAN	7291050050272
Valid tyre size	270 / 95 R 54
Alternative size 1	11.2R54
LI / SI / PR	159 A8 / 156 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Carcass properties	High Speed
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	100,98
Recommended rim size	10
Permitted rim size	9, 8
Maximum air pressure [bar].	6,00
Section width (mm)	285
Outer diameter of tyre [mm].	1900
Stat. radius (SLR) [mm]	903
Rolling circumference [mm].	5826
Tyre capacity 75% [ltr.]	167.25
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		6,00	
156 D	4000	65		6,00	