

TYRES

Product group	Tyres
Item number	15226707
Valid tyre size	VF 320 / 90 R 54
LI / SI / PR	168 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354 +



Bohnenkamp
■ ■ ● Moving Professionals

 **ALLIANCE**
ENGINEERED TO KEEP YOU AHEAD

Notes and features

- The Alliance Agriflex 354 is a row crop tyre with VF technology for tractors, self-propelled and towed field sprayers.
- As a VF tyre, it has 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belted construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.

Technical Informations

Item number	15226707
EAN	7291050077446
Valid tyre size	VF 320 / 90 R 54
LI / SI / PR	168 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354 +
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	105,00
Recommended rim size	DW11
Permitted rim size	W11, W10, W12
Maximum air pressure [bar].	4,40
Section width (mm)	311
Outer diameter of tyre [mm].	1950
Stat. radius (SLR) [mm]	911
Rolling circumference [mm].	5944
Tread depth (mm)	44,5
Number of lugs	36x2
Tyre capacity 75% [ltr.]	244.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		4,40	