

TYRES

Product group	Tyres
Item number	15226720
Valid tyre size	380 / 90 R 54
LI / SI / PR	155 A8 / 152 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	15226720
EAN	7291050060547
Valid tyre size	380 / 90 R 54
LI / SI / PR	155 A8 / 152 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	146,24
Recommended rim size	12
Permitted rim size	11, 13
Maximum air pressure [bar].	2,40
Section width (mm)	388
Outer diameter of tyre [mm].	2055
Stat. radius (SLR) [mm]	960
Rolling circumference [mm].	6287
Tread depth (mm)	47,0
Tyre capacity 75% [ltr.]	337.5
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40		2,40	
152 D	3550	65		2,40	