

TYRES

Product group	Tyres
Item number	15226723
Valid tyre size	380 / 90 R 54
LI / SI / PR	174 A8 / 171 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	15226723
EAN	7291050064026
Valid tyre size	380 / 90 R 54
Alternative size 1	14.9R54
LI / SI / PR	174 A8 / 171 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	160,63
Recommended rim size	12
Permitted rim size	11, 13
Maximum air pressure [bar].	4,80
Section width (mm)	388
Outer diameter of tyre [mm].	2055
Stat. radius (SLR) [mm]	962
Speed Radius Index (SRI)	1000
Rolling circumference [mm].	6257
Tread depth (mm)	47,0
Number of lugs	35x2
Tyre capacity 75% [litr.]	338
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
174 A8	6700	40		4,80	
171 D	6150	65		4,80	