

## TYRES

Product group	Tyres
Item number	15226727
Valid tyre size	IF 380 / 105 R 54
LI / SI / PR	180 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354



Bohnenkamp  
■ ■ ● Moving Professionals

 **ALLIANCE**

## Notes and features

- The Alliance Agriflex 354 is a row crop tyre with IF technology for tractors, self-propelled and towed field sprayers.
- As an IF tyre, it has 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre.
- This leads to optimal crop and soil protection.
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs.
- Its large contact area and steel belt construction also ensure traction and good ground pressure distribution.
- The tyre is characterised by durability, reduced fuel costs and ride comfort.

**Technical Informations**

Item number	15226727
EAN	7291050072281
Valid tyre size	IF 380 / 105 R 54
LI / SI / PR	180 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 354
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	192,49
Recommended rim size	13
Permitted rim size	12
Maximum air pressure [bar].	5,20
Section width (mm)	395
Outer diameter of tyre [mm].	2163
Stat. radius (SLR) [mm]	1003
Speed Radius Index (SRI)	1075
Rolling circumference [mm].	6548
Tread depth (mm)	48,0
Number of lugs	38x2
Tyre capacity 75% [ltr.]	414.23
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180 D	8000	65		5,20	