

TYRES

Product group	Tyres
Item number	15226737
Valid tyre size	750 / 50 R 26
LI / SI / PR	157 A8 / 151 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376





Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning properties.
- Nylon casing with reinforced steel belt.
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.



Technical Informations

Item number	15226737
EAN	7291050062824
Valid tyre size	750 / 50 R 26
LI / SI / PR	157 A8 / 151 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	151,83
Recommended rim size	25
Permitted rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	751
Outer diameter of tyre [mm].	1420
Stat. radius (SLR) [mm]	642
Rolling circumference [mm].	4319
Tread depth (mm)	40,0
Number of lugs	15x2
Tyre capacity 75% [ltr.]	482
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 A8	4125	40		2,40	
151 D	3450	65		2,40	