

TYRES

Product group	Tyres
Item number	15226740
Valid tyre size	750 / 65 R 26
LI / SI / PR	166 A8 / 163 B
TL/TT	TL
Brand	Alliance
Tread pattern	360





Notes and features

- Universal agricultural wide-base tyre for tractors, harvesters and other farm machinery.
- High air volume for increased load capacity and low ground pressure.
- Adapted lugs for massive traction and very good ride comfort at the same time.
- Strong radial casing with reinforced bead and sidewall for a long service life.



Technical Informations

Item number	15226740
EAN	7291050019750
Valid tyre size	750 / 65 R 26
Alternative size 1	28LR26
LI / SI / PR	166 A8 / 163 B
TL/TT	TL
Brand	Alliance
Tread pattern	360
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	232,73
Recommended rim size	25
Permitted rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	751
Outer diameter of tyre [mm].	1623
Stat. radius (SLR) [mm]	723
Rolling circumference [mm].	4817
Tread depth (mm)	55,0
Lug width (mm)	55
Tyre capacity 75% [ltr.]	648.75
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A8	5300	40		2,40	
163 B	4875	50		2,40	