

## **TYRES**

Product group	Tyres
Item number	15226756
Valid tyre size	600 / 65 R 28
LI / SI / PR	150 A8 / 147 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365





## Notes and features

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large contact area.
- Lug shape and arrangement allows optimum traction power distribution.
- With 65 km/h approval, suitable for frequent road use.



## **Technical Informations**

Item number	15226756
EAN	7291050053020
Valid tyre size	600 / 65 R 28
LI / SI / PR	150 A8 / 147 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	143,93
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	594
Outer diameter of tyre [mm].	1484
Stat. radius (SLR) [mm]	669
Rolling circumference [mm].	4509
Guarantee period	7 years
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		1,60	
147 D	3075	65		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.