

TYRES

Product group	Tyres	
Item number	15226757	
Valid tyre size	440 / 65 R 28	
LI / SI / PR	138 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agristar 365	





Notes and features

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large contact area.
- Lug shape and arrangement allows optimum traction power distribution.
- With 65 km/h approval, suitable for frequent road use.



Technical Informations

Item number	15226757
EAN	8903635019169
Valid tyre size	440 / 65 R 28
LI / SI / PR	138 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	84,60
Recommended rim size	14
Maximum air pressure [bar].	2,40
Section width (mm)	441
Outer diameter of tyre [mm].	1283
Stat. radius (SLR) [mm]	590
Rolling circumference [mm].	3869
Tread depth (mm)	44,4
Number of lugs	20x2
Tyre capacity 75% [ltr.]	182.55
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 D	2360	65		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.