

## **TYRES**

Product group	Tyres	
Item number	15226758	
Valid tyre size	VF 600 / 65 R 28 NRO	
LI / SI / PR	163 D  TL  Alliance	
TL/TT		
Brand		
Tread pattern	Agristar VF 365	





## Notes and features

- The Alliance 365 as a VF tyre is a modern agricultural tyre for powerful tractors up to 250 hp.
- The VF technology (Very High Flexion) enables up to 40% higher loading capacity at the same inflation pressure and speed.
- Due to the large contact area and low inflation pressure, the soil is optimally protected.
- The shape and arrangement of lugs allow optimum traction power distribution.
- Thanks to the NRO technology (Narrow Rim Option), the tyre can also be mounted on a narrower rim than e.g. IF and VF tyres of the same size in other versions or from other suppliers.
- As the tyre is approved for speeds up to 65 km/h, it is also suitable for road transport.



## **Technical Informations**

Item number	15226758
EAN	8903635022701
Valid tyre size	VF 600 / 65 R 28 NRO
LI / SI / PR	163 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar VF 365
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	161,00
Recommended rim size	20
Permitted rim size	21
Maximum air pressure [bar].	2,00
Section width (mm)	615
Outer diameter of tyre [mm].	1491
Stat. radius (SLR) [mm]	648
Rolling circumference [mm].	4436
Tread depth (mm)	55,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	390
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 D	4875	65		2,00	