

## **TYRES**

Product group	Tyres	
Item number	15226760	
Valid tyre size	IF 1050 / 50 R 32 CFO	
LI / SI / PR	195 A8	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Multistar 376	





## Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning properties.
- Nylon casing with reinforced steel belt.
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.



## **Technical Informations**

Item number	15226760
EAN	7291050072595
Valid tyre size	IF 1050 / 50 R 32 CFO
LI / SI / PR	195 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	405,00
Recommended rim size	36
Maximum air pressure [bar].	4,00
Section width (mm)	1050
Outer diameter of tyre [mm].	1860
Stat. radius (SLR) [mm]	831
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5651
Tread depth (mm)	43,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	1266
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
195 A8	12150	40		4,00	