

TYRES

Product group	Tyres
Item number	15226760
Valid tyre size	IF 1050 / 50 R 32 CFO
LI / SI / PR	195 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376



Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning properties.
- Nylon casing with reinforced steel belt.
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.

Technical Informations

Item number	15226760
EAN	7291050072595
Valid tyre size	IF 1050 / 50 R 32 CFO
LI / SI / PR	195 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	405,00
Recommended rim size	36
Maximum air pressure [bar].	4,00
Section width (mm)	1050
Outer diameter of tyre [mm].	1860
Stat. radius (SLR) [mm]	831
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5651
Tread depth (mm)	43,0
Number of lugs	18x2
Tyre capacity 75% [litr.]	1266
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
195 A8	12150	40		4,00	