# Bohnenkamp Moving Professionals

#### **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 15226761       |
| Valid tyre size | 900 / 60 R 32  |
| LI / SI / PR    | 194 A8 / 191 D |
| TL/TT           | TL             |
| Brand           | Alliance       |
| Tread pattern   | Multistar 376  |





#### Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient • spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning ٠ properties.
- Nylon casing with reinforced steel belt. •
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.

# Bohnenkamp Moving Professionals

### **Technical Informations**

| Item number                  | 15226761       |
|------------------------------|----------------|
| EAN                          | 8903635021841  |
| Valid tyre size              | 900 / 60 R 32  |
| Alternative size 1           | 35.5LR32       |
| LI / SI / PR                 | 194 A8 / 191 D |
| TL/TT                        | TL             |
| Brand                        | Alliance       |
| Tread pattern                | Multistar 376  |
| Carcass properties           | Steel Belted   |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 388,00         |
| Recommended rim size         | 27             |
| Maximum air pressure [bar].  | 4,40           |
| Section width (mm)           | 869            |
| Outer diameter of tyre [mm]. | 1894           |
| Stat. radius (SLR) [mm]      | 850.00         |
| Rolling circumference [mm].  | 5645           |
| Tread depth (mm)             | 56,8           |
| Number of lugs               | 19x2           |
| Tyre capacity 75% [ltr.]     | 1056           |
| Guarantee period             | 10 years       |
| E-Ready                      | No             |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 194 A8 | 11800              | 40           |               | 4,40                        |              |
| 191 D  | 10900              | 65           |               | 4,40                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.