

TYRES

Product group	Tyres
Item number	15226763
Valid tyre size	540 / 65 R 30
LI / SI / PR	168 A8
TL/TT	TL
Brand	Alliance
Tread pattern	360



Notes and features

- Universal agricultural wide-base tyre for tractors, harvesters and other farm machinery.
- High air volume for increased load capacity and low ground pressure.
- Adapted lugs for massive traction and very good ride comfort at the same time.
- Strong radial casing with reinforced bead and sidewall for a long service life.

Technical Informations

Item number	15226763
EAN	7291050068567
Valid tyre size	540 / 65 R 30
LI / SI / PR	168 A8
TL/TT	TL
Brand	Alliance
Tread pattern	360
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	135,90
Recommended rim size	16
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	560
Outer diameter of tyre [mm].	1486
Stat. radius (SLR) [mm]	670
Rolling circumference [mm].	4421
Tyre capacity 75% [ltr.]	343.5
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A8	5600	40	Free Rolling	2,40	
	4000	40	Drive Wheel	2,40	