

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 15226764 |
| Valid tyre size | VF 800 / 65 R 32 |
| LI / SI / PR | 181 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agristar 375 |



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 15226764 |
| EAN | 7291050073547 |
| Valid tyre size | VF 800 / 65 R 32 |
| LI / SI / PR | 181 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agristar 375 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 333,00 |
| Recommended rim size | 27 |
| Maximum air pressure [bar]. | 2,00 |
| Section width (mm) | 800 |
| Outer diameter of tyre [mm]. | 1853 |
| Stat. radius (SLR) [mm] | 807 |
| Speed Radius Index (SRI) | 875 |
| Rolling circumference [mm]. | 5531 |
| Tread depth (mm) | 60,0 |
| Number of lugs | 20x2 |
| Tyre capacity 75% [ltr.] | 907 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 181 D | 8250 | 65 | | 2,00 | |