

TYRES

Product group	Tyres
Item number	15226784
Valid tyre size	1050 / 50 R 32
LI / SI / PR	178 A8 / 172 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376



Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning properties.
- Nylon casing with reinforced steel belt.
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.

Technical Informations

Item number	15226784
EAN	7291050060653
Valid tyre size	1050 / 50 R 32
LI / SI / PR	178 A8 / 172 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	373,15
Recommended rim size	36
Maximum air pressure [bar].	2,40
Section width (mm)	1050
Outer diameter of tyre [mm].	1870
Stat. radius (SLR) [mm]	833
Rolling circumference [mm].	5686
Tread depth (mm)	42,5
Number of lugs	20x2
Tyre capacity 75% [ltr.]	1274
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40		2,40	
172 D	6300	65		2,40	