

TYRES

Product group	Tyres
Item number	15226801
Valid tyre size	650 / 65 R 38
LI / SI / PR	166 A8 / 163 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365



Notes and features

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large contact area.
- Lug shape and arrangement allows optimum traction power distribution.
- With 65 km/h approval, suitable for frequent road use.

Technical Informations

Item number	15226801
EAN	7291050020947
Valid tyre size	650 / 65 R 38
LI / SI / PR	166 A8 / 163 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	230,95
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	658
Outer diameter of tyre [mm].	1825
Stat. radius (SLR) [mm]	837
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5548
Tread depth (mm)	58,0
Number of lugs	21x2
Lug width (mm)	49-58
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 A8	5300	40		2,40	
163 D	4875	65		2,40	