

## **TYRES**

| Product group   | Tyres           |
|-----------------|-----------------|
| Item number     | 15226809        |
| Valid tyre size | 710 / 70 R 38   |
| LI / SI / PR    | 175 A2 / 168 A8 |
| TL/TT           | TL              |
| Brand           | Alliance        |
| Tread pattern   | Forestry 360    |





## Notes and features

- The Alliance Forestry 360 is a forestry tyre for light forestry applications.
- Its low lug angles provide excellent traction.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls and tread pattern, the tyre is particularly robust.
- The tyre can also be used for agro-industrial applications.



## **Technical Informations**

| Item number                  | 15226809        |
|------------------------------|-----------------|
| EAN                          | 7291050065573   |
| Valid tyre size              | 710 / 70 R 38   |
| LI / SI / PR                 | 175 A2 / 168 A8 |
| TL/TT                        | TL              |
| Brand                        | Alliance        |
| Tread pattern                | Forestry 360    |
| TRA Code                     | R1-W            |
| Carcass properties           | Steel Belted    |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 106         |
| Nettogewicht [kg] (gültig)   | 334,46          |
| Recommended rim size         | 23              |
| Maximum air pressure [bar].  | 2,40            |
| Section width (mm)           | 716             |
| Outer diameter of tyre [mm]. | 1940            |
| Stat. radius (SLR) [mm]      | 898             |
| Rolling circumference [mm].  | 5897            |
| Tread depth (mm)             | 55,0            |
| Number of lugs               | 23x2            |
| Tyre capacity 75% [ltr.]     | 817.5           |
| E-Ready                      | No              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 175 A2 | 6900               | 10           |               | 2,40                        |              |
| 168 A8 | 5600               | 40           |               | 2,40                        |              |