

TYRES

Product group	Tyres
Item number	15226812
Valid tyre size	650 / 65 R 38
LI / SI / PR	174 A8 / 171 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365



Notes and features

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large contact area.
- Lug shape and arrangement allows optimum traction power distribution.
- With 65 km/h approval, suitable for frequent road use.

Technical Informations

Item number	15226812
EAN	8903635017158
Valid tyre size	650 / 65 R 38
LI / SI / PR	174 A8 / 171 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	218,86
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	3,60
Section width (mm)	650
Outer diameter of tyre [mm].	1830
Stat. radius (SLR) [mm]	843
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5690
Tread depth (mm)	58,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	616
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
174 A8	6700	40		3,60	
171 D	6150	65		3,60	