

TYRES

Product group	Tyres
Item number	15226818
Valid tyre size	650 / 65 R 42
LI / SI / PR	172 A2 / 165 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360



Notes and features

- The Alliance Forestry 360 is a forestry tyre for light forestry applications.
- Its low lug angles provide excellent traction.
- Due to the strong nylon casing with steel breakers, high undertread gauge and reinforced sidewalls and tread pattern, the tyre is particularly robust.
- The tyre can also be used for agro-industrial applications.

Technical Informations

Item number	15226818
EAN	7291050065146
Valid tyre size	650 / 65 R 42
LI / SI / PR	172 A2 / 165 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 360
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	285,80
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	655
Outer diameter of tyre [mm].	1950
Stat. radius (SLR) [mm]	900
Rolling circumference [mm].	5869
Tread depth (mm)	52,0
Number of lugs	24x2
Tyre capacity 75% [litr.]	670.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A2	6300	10		2,40	
165 A8	5150	40		2,40	