

TYRES

Product group	Tyres
Item number	15226829
Valid tyre size	650 / 65 R 42
LI / SI / PR	161 A8 / 158 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365





Notes and features

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp.
- Very gentle tillage due to high air volume and large contact area.
- Lug shape and arrangement allows optimum traction power distribution.
- With 65 km/h approval, suitable for frequent road use.



Technical Informations

Item number	15226829
EAN	7291050053068
Valid tyre size	650 / 65 R 42
LI / SI / PR	161 A8 / 158 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 365
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	231.69
Recommended rim size	DW20B
Permitted rim size	DW21B, DW23B
Maximum air pressure [bar].	1,60
Section width (mm)	667
Outer diameter of tyre [mm].	1945
Stat. radius (SLR) [mm]	882
Rolling circumference [mm].	5911
Tread depth (mm)	52,0
Number of lugs	22x2
Lug width (mm)	56,5
Tyre capacity 75% [ltr.]	699
Guarantee period	7 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 A8	4625	40		1,60	
158 D	4250	65		1,60	