

TYRES

Product group	Tyres
Item number	15226845
Valid tyre size	620 / 70 R 46
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376



Notes and features

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors.
- 45° lug angle for high traction with good self-cleaning properties.
- Nylon casing with reinforced steel belt.
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble.

Technical Informations

Item number	15226845
EAN	7291050062473
Valid tyre size	620 / 70 R 46
LI / SI / PR	162 A8 / 159 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multistar 376
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	245,19
Recommended rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	620
Outer diameter of tyre [mm].	2045
Stat. radius (SLR) [mm]	931
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6146
Tread depth (mm)	56,0
Number of lugs	22x2
Tyre capacity 75% [litr.]	688
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		1,60	
159 D	4375	65		1,60	